

DECLARATION OF PERFORMANCE No. 02/MP/VP/2021

1. Unique identification code of the product-type:

MultiPlate Structures (also use the name **ViaPlate**): **VM** (1-50), **VN** (1-35), **VT** (1-35), **VR** (1-25), **VF** (1-8), **VC** (1-80), **VE** (1-35), **VS** (1-30), **VH** (1-42), **VA** (1-170), **VB** (1-30), **VBL** (1-42), **VBH** (1-20), **VG** (1-35), **V** (1-47), **BC** (1-27), **PA** (1-100), **L** (1-59), **P** (1-34), **C** (1-34), **PE** (1-34), **E** (1-34), **U** (1-31), **G** (1-30), **UH** (1-15), **GH** (1-10), **UL** (1-21), **GL** (1-20), **HE** (1-36), **LE** (1-36), **A** (1-47)

Profiles produced range is expanded to include profiles resulting from the additional customer requirements (design, specification) – **Spec.**

2. Intended use/es:

Structures Multiplate MP150 and MP200 (ViaPlate) are designed to build bridges and engineering used to carry water courses, wildlife, pedestrian and vehicular traffic and to carry out the installation of equipment (pipelines), cables for road and railway embankments and tunnels working as. They can be used for all load classes of roads and railways. They can also be used to reinforce, renovation and reconstruction of existing bridges and engineering, with the ground or concrete filling the space between the existing structure and the construction of Multiplate MP150 and MP200 (ViaPlate).

3. Manufacturer: **ViaCon Sp. z o. o., ul. Przemysłowa 6, 64-130 Rydzyna, Polska**

4. Authorized representative: -

5. System/s of AVCP: **2+**

6a. Harmonized standard: **EN 1090-1+A1:2012**

Notified body/ies: **ITC Nr 1023-CPR-0640 F**

7. Declared performance/s:

Essential characteristics	Declared performance	Harmonized technical specification
Tolerances on dimensions and shape	EN 1090-2	PN-EN 1090-1+A1:2012
Weldability	Steel S235JR, S355JR EN 10025-2	PN-EN 1090-1+A1:2012
Fracture toughness/impact resistance	Min 27 J	PN-EN 1090-1+A1:2012
Reaction to fire	A1	PN-EN 1090-1+A1:2012
Release of cadmium and its compounds	NPD	PN-EN 1090-1+A1:2012
Radioactivity	NPD	PN-EN 1090-1+A1:2012
Durability	Hot Dip Galvanizing EN 1461 Surface painted EN 12944	PN-EN 1090-1+A1:2012
Load bearing capacity	NPD	PN-EN 1090-1+A1:2012
Fatigue strenght	NPD	PN-EN 1090-1+A1:2012

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

Technical Documentation MultiPlate Constructions (ViaPlate)

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Tomasz Poprawski

Tomasz Poprawski

Rydzyna on 12.11.2021

Dyrektor Produkcji

ViaCon Polska Sp.zo.o.

ul. Przemysłowa 6, 64-130 Rydzyna

tel. (65) 5254545, fax (65) 5254555

REGON410351222, NIP 697-17-10-977

-20-

ViaCon Polska Sp. z o.o.

ul. Przemysłowa 6; 64-130 Rydzyna k/ Leszna; tel.: 65 525 45 45; fax: 65 525 45 55 ; e-mail: office@viacon.pl

Sąd Rejonowy Poznań-Nowe Miasto i Wilda IX Wydz. Gosp., KRS 000093391;

REGON 410351222; NIP 697 17 10 977; Kapitał zakładowy: 1 420 000 PLN

www.viacon.pl