



## Case Study

# Firewater tank solution secures fire protection at airport in Norway

ViaCon delivered a customised 210 m<sup>3</sup> firewater tank with an integrated pump room to meet fire protection requirements in an airport project in Norway.

## The Challenge

In an airport project in Norway, the contractor needed a reliable firewater solution to comply with fire protection regulations. The system had to provide 210 m<sup>3</sup> of firewater storage and deliver a required

flow of 50 litres per second for one hour. In addition to storage capacity, the project required an integrated pumping solution capable of supporting dependable operation in a critical infrastructure environment.

Learn more at [viacongroup.com](https://viacongroup.com)

**VIACON**

## The Solution

To meet the project requirements, ViaCon delivered a customised firewater tank solution in Norway based on PE-coated, hot-dip galvanised corrugated steel.

The solution consisted of a D3000 tank with a length of 36 metres and an integrated pump room. The system was equipped with:

- 2 pumps with a flow capacity of 50 l/s
- control units for the pumps
- level sensors
- an electronic inlet filling valve
- flotation valves for operation in case of power failure
- and sprinkler suction pipes connected to external sprinkler pumps

This provided the customer with a complete and reliable firewater solution tailored to the specific needs of the airport project.

## The ViaCon advantage

By choosing ViaCon's firewater tank solution, the customer received a customised system combining water storage and pumping functions in one integrated installation.

In addition to meeting the required firewater volume and flow performance, the solution offers a low CO<sub>2</sub> footprint and an estimated service life of more than 80 years. This provides a durable and efficient alternative for critical fire protection applications.

## Tekniska specifikationer

**Application:** Firewater tank for airport project

**Location:** Norway

**Storage volume:** 210 m<sup>3</sup>

**Tank type:** PE-coated, hot-dip galvanised corrugated steel tank



**Diameter:** D3000

**Length:** 36 m

**Pump room:** Integrated

**Pumps:** 2 pcs

**Pump capacity:** 50 l/s

**Pump controls:** Included

**Level sensors:** Included

**Inlet valve:** Electronic filling valve

**Backup function:** Flotation valves in case of electricity failure

**Sprinkler connection:** Suction pipes connected to external sprinkler pumps

## Read more at

[www.viaconacademy.com](http://www.viaconacademy.com)



## Contact us

[info@viacongroup.com](mailto:info@viacongroup.com)

**VIACON**

[www.viacongroup.com](http://www.viacongroup.com)

Björklundabacken 3, 436 57 Hovås, Sweden